

# Alarm Box

## AL-1112

- Supports DirectIP NVR
- Supports IDIS Solution Suite
- 4 Relay Output
- 8 Alarm Input
- DC Output for Small Power Devices
- LED Indicator of Alarm Status



### SPECIFICATIONS

| INTERFACE             |  |
|-----------------------|--|
| Alarm Input           | 8 Digital-Input<br>- Dry contact, Wet contact<br>High : Open or DC 5V ~ DC 30V<br>Low : Short or DC 0V ~ DC 1.8V |
| Alarm Output          | 4 Relay-out<br>- NC, NO, COMMON  |
| Power Output          | 12VDC(300mA), 5VDC(400mA)  |
| Ethernet              | 10/100Mbps   |
| DirectIP Supported    | Yes  |
| USB                   | Yes (Spare)  |
| GENERAL               |  |
| Dimension (W x H x D) | 200mm x 44mm x 154.7mm (7.9" x 1.7" x 6.1")  |
| Unit Weight           | 0.77kg (1.7lb)   |
| Operating Temperature | -10°C ~ +50°C (+14°F ~ +122°F)<br>*Starting up at above 0°C (32°F)   |
| PoE(class)            | Yes(IEEE 802.3at Class 4)  |
| Power source          | 12VDC, 24VAC, PoE  |
| Power Consumption     | 12V=, 2.19A, 26.3W<br>24V-, 1.57A, 22.9W, 50/60Hz<br>PoE, IEEE 802.3at(Class 4), 23W                             |
| Approvals             | FCC, CE, KC  |

### DIMENSIONS

(Unit - mm)

