

DC-D1123R

- Easy installation with DirectIP NVR
- HD (720p) resolution
- Vari-focal lens(f=3.3 - 10mm)
- micro SD/SDHC
- Two-way audio
- Alarm in / out
- PoE(IEEE 802.3af class 2), 12V DC
- Day&night (ICR)
- IR LED (Distance : 20m)
- 3-axis mechanical design for installation
- Supports ONVIF



SPECIFICATIONS

VIDEO																													
Image Sensor	1/2.7" CMOS																												
Max. Resolution	1280 x 720																												
Scanning Mode	Progressive Scan																												
Lens type	Vari-focal																												
Focal Length	f=3.3 - 10mm																												
Aperture	F1.5 - 2.5																												
Iris Control	DC Auto Iris																												
Angular Field of View	Wide : 105.5°(H), 55.4°(V), 125.3°(D) Tele : 35.3°(H), 19.7°(V), 40.4°(D)																												
Pan/Tilt Range	Pan: -167° ~ 167°, Tilt: 0° ~ 80°, Rotate: -176° ~ 176°																												
Min. Illumination	COLOR : 0.6 lux @ F1.5 B/W : 0 lux (IR LED ON)																												
S/N Ratio	more than 45dB																												
Dynamic Range	more than 70dB																												
Electronic Shutter Speed	Auto / Manual (1/30 ~ 1/8000), Anti-Flicker, Slow Shutter(1/7.5,1/15)																												
Day & Night	IR cut filter with auto switch																												
IR Distance (LEDs)	20m (18ea)																												
Image Setting	Configurable Exposure, White Balance, Sharpness																												
Digital Noise Reduction	Configurable 2DNR/3DNR																												
Backlight Compensation	On / Off / HSBLC																												
Image Stabilizer	-																												
Privacy Masking	16 Zones																												
Intelligent Video	Video Motion Detection, Active Tampering Alarm, Trip Zone																												
Video Out	1 Terminal Block																												
NETWORK																													
	<table border="1"> <thead> <tr> <th>DirectIP Mode</th> <th>Compatibility Mode</th> </tr> </thead> <tbody> <tr> <td>Video Compression</td> <td>H.264(MP), M-JPEG</td> </tr> <tr> <td>Bitrate Control</td> <td>H.264 - CBR / VBR</td> </tr> <tr> <td>Max. Frame Rate</td> <td>30fps : 1280 x 720</td> </tr> <tr> <td>Audio Compression</td> <td>G.726, G.711</td> </tr> <tr> <td>Two-way audio</td> <td>Yes</td> </tr> <tr> <td>IP Camera Protocol</td> <td>DirectIP IDIS ONVIF Profile S</td> </tr> <tr> <td>Supported Resolution</td> <td>1280x720, 704x480, 640x 360, 352x240 1280x720, 704x480, 352x240</td> </tr> <tr> <td>Multi-Video Streaming</td> <td>Quadruple streaming Triple streaming</td> </tr> <tr> <td>Network Protocols</td> <td>Direct IP Protocol RTP/RTSP/TCP, RTP/RTSP/HTTP/TCP, RTP/UDP RTSP/TCP, HTTP, HTTPS, FTP, SNTp, SMTP, FEN, mDNS, uPNP</td> </tr> <tr> <td>Security</td> <td>SSL Encryption Multi-User Authority, IEEE 802.1x IP Filtering, HTTPS, SSL Encryption</td> </tr> <tr> <td>Remote Access Client</td> <td>DirectIP™ NVR connection IDIS Web, IDIS Mobile, IDIS Solution Suite</td> </tr> <tr> <td>Ethernet</td> <td>RJ45(10/100BASE-T)</td> </tr> <tr> <td>Edge Storage</td> <td>micro SD/SDHC</td> </tr> </tbody> </table>	DirectIP Mode	Compatibility Mode	Video Compression	H.264(MP), M-JPEG	Bitrate Control	H.264 - CBR / VBR	Max. Frame Rate	30fps : 1280 x 720	Audio Compression	G.726, G.711	Two-way audio	Yes	IP Camera Protocol	DirectIP IDIS ONVIF Profile S	Supported Resolution	1280x720, 704x480, 640x 360, 352x240 1280x720, 704x480, 352x240	Multi-Video Streaming	Quadruple streaming Triple streaming	Network Protocols	Direct IP Protocol RTP/RTSP/TCP, RTP/RTSP/HTTP/TCP, RTP/UDP RTSP/TCP, HTTP, HTTPS, FTP, SNTp, SMTP, FEN, mDNS, uPNP	Security	SSL Encryption Multi-User Authority, IEEE 802.1x IP Filtering, HTTPS, SSL Encryption	Remote Access Client	DirectIP™ NVR connection IDIS Web, IDIS Mobile, IDIS Solution Suite	Ethernet	RJ45(10/100BASE-T)	Edge Storage	micro SD/SDHC
DirectIP Mode	Compatibility Mode																												
Video Compression	H.264(MP), M-JPEG																												
Bitrate Control	H.264 - CBR / VBR																												
Max. Frame Rate	30fps : 1280 x 720																												
Audio Compression	G.726, G.711																												
Two-way audio	Yes																												
IP Camera Protocol	DirectIP IDIS ONVIF Profile S																												
Supported Resolution	1280x720, 704x480, 640x 360, 352x240 1280x720, 704x480, 352x240																												
Multi-Video Streaming	Quadruple streaming Triple streaming																												
Network Protocols	Direct IP Protocol RTP/RTSP/TCP, RTP/RTSP/HTTP/TCP, RTP/UDP RTSP/TCP, HTTP, HTTPS, FTP, SNTp, SMTP, FEN, mDNS, uPNP																												
Security	SSL Encryption Multi-User Authority, IEEE 802.1x IP Filtering, HTTPS, SSL Encryption																												
Remote Access Client	DirectIP™ NVR connection IDIS Web, IDIS Mobile, IDIS Solution Suite																												
Ethernet	RJ45(10/100BASE-T)																												
Edge Storage	micro SD/SDHC																												
ALARM & EVENT																													
Trigger Event	Motion Detection, Alarm in, Audio detection, Tampering, TripZone																												
Event Buffering (Pre & Post)	yes (up to 60MB)																												
Event Notification	Remote S/W, Email (with Image)																												
Audio In/ Out	Line-in 1ea / Line-out 1ea																												
Alarm In/ Out	Input 1ea / Output 1ea																												
ENVIRONMENTAL																													
Vandal-proof Casing	-																												
Out-door Ready	-																												
Operating Temperature	-10°C ~ +50°C (+14°F ~ +122°F) *Starting up at above 0°C (32°F)																												
Operating Humidity	0% ~ 90%																												
ELECTRICAL																													
Power Source	12VDC, PoE(IEEE 802.3af class 2)																												
Power Consumption	5.6W																												
Approvals	FCC, CE, KC																												
MECHANICAL																													
Dimensions	Ø160mm x 122mm (Ø6.3" x 4.81")																												
Weight	0.51 kg (1.13 lb)																												

DIMENSIONS

(Unit - mm)



ACCESSORIES(OPTIONAL)



ACCESSORIES CONFIGURATION TREE

