

12MP Vandal-Resistant IR Dome Camera with Heater

DC-D3C33HRX

- Easy installation with DirectIP NVR
- 12MP (4000 x 3000) resolution
- Motorized Vari-focal lens (f=4.5 - 10mm)
- micro SD/SDHC/SDXC, Smart Failover (Up to 128GB)
- Two-way audio
- Alarm in / out
- IK10 / IP67 supports
- Built-in heater
- PoE (IEEE 802.3af Class 3), 12VDC
- Day and night (ICR)
- True wide dynamic range (WDR)
- IR LED (Distance : 30m)
- 3-axis mechanical design for installation
- Supports ONVIF



SPECIFICATIONS

VIDEO		
Image Sensor	1/1.7" CMOS	
Max. Resolution	4000 x 3000	
Scanning Mode	Progressive Scan	
Lens Type	Motorized Vari-focal	
Focal Length	f=4.5 - 10mm	
Aperture	F=1.6 - 2.6	
Iris Control	P-Iris	
Angular Field of View	[8M mode] Wide : 90.2° (H), 48.5° (V), 106.2° (D) Tele : 41.6° (H), 23.3° (V), 47.8° (D) [12M mode] Wide : 94.6° (H), 68.5° (V), 125.2° (D) Tele : 43.4° (H), 32.4° (V), 54° (D)	
Pan / Tilt Range	Pan : -176° ~ 176°, Tilt : 0° ~ 65°, Rotate : -90° ~ 90°	
Min. Illumination	Color : 0.3 Lux @ F1.6 B/W : 0 Lux (IR LED On)	
Dynamic Range	120dB (True WDR)	
Electronic Shutter Speed	Auto / Manual (1/30 ~ 1/8000), Anti-Flicker, Slow Shutter (1/7.5, 1/15)	
Day and Night	IR Cut Filter with Auto Switch	
IR Distance (LEDs)	30 m / 98.4 ft (6 ea)	
Image Setting	Configurable Exposure, White Balance, Sharpness	
Digital Noise Reduction	Configurable 2DNR / 3DNR	
Backlight Compensation	On / Off / HSBLC	
Image Stabilizer	-	
De-fog	On / Off	
Privacy Masking	8 Zones	
Intelligent Video	Video Motion Detection, Active Tampering Alarm, Trip Zone	
Video Out	1 BNC (Accessory)	
NETWORK		
	DirectIP Mode	Compatibility Mode
Video Compression	H.265, H.264 (MP), M-JPEG	
Intelligent Codec	Supported	
Bitrate Control	H.264 - CBR / VBR, H.265 - CBR / VBR	
Audio Compression	ADPCM 16K, G.726, G.711 u-Law, G.711 a-Law	
Two-way Audio	Yes	
IP Camera Protocol	DirectIP	IDIS ONVIF Profile S
Max. Frame Rate	15ips : 3840 x 2160	30ips : 3840 x 2160 15ips : 4000 x 3000
Supported Resolution	3840 x 2160, 1920 x 1080, 1280 x 720, 640 x 360, 320 x 180	12MP mode : 4000 x 3000, 2592 x 1944, 1280 x 960, 640 x 480, 320 x 240 8MP mode : 3840 x 2160, 1920 x 1080, 1280 x 720, 640 x 360, 320 x 180
Multi-video Streaming	Quadruple Streaming	Quadruple Streaming
Network Protocols	DirectIP Protocol	RTP/RTSP/TCP, RTP/RTSP/HTTP/TCP, RTP/UDP RTSP/TCP, HTTP, HTTPS, FTP, SMTP, FEN, mDNS, uPNP
Security	SSL Encryption	Multi-user Authority, IEEE 802.1x, IP Filtering, HTTPS, SSL Encryption
Remote Access Client	DirectIP NVR Connection	IDIS Web, IDIS Mobile, IDIS Solution Suite
Ethernet	RJ45 (10/100/1000 BASE-T)	
Recording Session Buffer	Yes (Up to 60MB)	
Edge Storage	micro SD/SDHC/SDXC, Smart Failover (Up to 128GB)	
ALARM AND EVENT		
Trigger Event	Motion Detection, Audio Detection, Alarm In, Tampering, Trip Zone	
Event Notification	Remote S/W, Email (With Image)	
Audio In / Out	Line-in 1ea / Line-out 1ea	
Alarm In / Out	Input 1ea / Output 1ea	
ENVIRONMENTAL		
Vandal Proof Casing	IK10	
Outdoor Ready	IP67, Heater	
Operating Temperature	-40°C ~ +60°C (-40°F ~ +140°F) *Starting up at above -20°C (-4°F)	
Operating Humidity	0% ~ 90%	
ELECTRICAL		
Power Source	12VDC, PoE (IEEE 802.3af Class 3)	
Power Consumption	11.4W	
Approvals	FCC, CE, KC	
MECHANICAL		
Dimensions	Ø160mm x 128.5mm (Ø6.30" x 5.06")	
Weight	1.21kg (2.66lb)	

DIMENSIONS

(Unit - mm)



ACCESSORIES (OPTIONAL)



ACCESSORIES CONFIGURATION TREE

