

5MP Vandal-Resistant IR Dome Camera

DC-D4536HRX-A



- Easy installation with DirectIP NVR
- 5MP (2592 x 1944) Resolution
- Motorized Vari-focal Lens (f = 3.0 - 13.5 mm)
- micro SD/SDHC/SDXC
- Alarm In / Out
- IK10 / IP67
- Built-in Heater
- PoE (IEEE 802.3af Class 3), 12V DC
- Day and Night (ICR)
- True Wide Dynamic Range (WDR)
- IR LED (Distance : 30 m / 98.4 ft)
- 3-axis Mechanical Design for Installation
- Supports ONVIF



SPECIFICATIONS

VIDEO	
Image Sensor	1/2.8" CMOS
Max. Resolution	2592 x 1944
Scanning Mode	Progressive Scan
Lens Type	Motorized Vari-focal
Focal Length	f = 3.0 - 13.5 mm
Aperture	F1.4 - 3.2
Iris Control	DC IRIS
Angular Field of View	Wide : 91°(H) 66°(V) 120°(D) Tele : 31°(H) 23°(V) 38°(D)
Pan / Tilt Range	Pan: -175° ~ 175°, Tilt: 0° ~ 67°, Rotate: -177° ~ 177°
Min. Illumination	Color : 0.15 Lux @ F1.4 B/W : 0 Lux (IR LED On)
Dynamic Range	120dB (True WDR)
Electronic Shutter Speed	Auto / Manual (1/30 ~ 1/10,000), Anti-Flicker, Slow Shutter (1/7.5, 1/15)
Day and Night	IR Cut Filter with Auto Switch
IR Distance (LEDs)	30 m / 98.4 ft (6ea)
Image Setting	Exposure, White Balance, Self-Adjusting Video Mode (Sharpness, Contrast, Colors, Brightness Control)
Digital Noise Reduction	Configurable 2DNR/3DNR
Backlight Compensation	On / Off
Image Stabilizer	-
De-fog	-
Privacy Masking	8 Zones
Intelligent Video	Video Motion Detection, Active Tampering Alarm, Trip Zone
Video Out	-
NETWORK	
	DirectIP Mode
Video Compression	H.265, H.264 (MP) M-JPEG
Intelligent Codec	Supported
Bitrate Control	H.265 - CBR / VBR, H.264 - CBR / VBR
Audio Compression	-
Two-way Audio	-
IP Camera Protocol	DirectIP 2.0, ONVIF Profile S
Max. Frame Rate	4:3 mode : 30ips : 2592 x 1944 (WDR) 16:9 mode : 30ips : 2592 x 1456 (WDR)
Supported Resolution	4:3 : 2592 x 1944, 1920 x 1440, 1280 x 960, 640 x 480 16:9 : 2592 x 1456, 1920 x 1080, 1280 x 720, 640 x 360
Multi-video Streaming	Quadruple Streaming
Network Protocols	DirectIP 2.0 Protocol, IPv4, IPv6, RTP/RTSP/TCP, RTP/RTSP/HTTP/TCP, RTP/UDP RTSP/TCP, HTTP, HTTPS, FTP, SMTP, FEN, mDNS, uPNP, SNMPv2
Security	SSL Encryption, Multi-user Authority, IEEE 802.1x, IP Filtering, HTTPS
Remote Access Client	DirectIP NVR Connection, IDIS Web, IDIS Mobile, IDIS Solution Suite
Ethernet	RJ45 (10/100BASE-T)
Recording Session Buffer (NLTSrec)	Yes (Up to 60MB)
Edge Storage	micro SD/SDHC/SDXC, Smart Failover (Up to 256GB)
ALARM AND EVENT	
Trigger Event	Motion Detection, Alarm in, Tampering, Trip Zone
Event Notification	Remote S/W, Email (with Image)
Audio In / Out	-
Alarm In / Out	1 / 1
ENVIRONMENTAL	
Vandal Proof Casing	IK10
Outdoor Ready	IP67, Heater
Operating Temperature	-40°C ~ +55°C (-40°F ~ +131°F) *Starting up at above -20°C (-4°F)
Operating Humidity	0% ~ 90%
ELECTRICAL	
Power Source	12VDC, PoE IEEE 802.3af (Class 3)
Power Consumption	12V=, 1.1A, 13.2W PoE, IEEE 802.3af (Class 3), 11W
Approvals	FCC, CE, KC
MECHANICAL	
Dimensions	Ø155 mm x 104.4mm (Ø6.11" x 4.11")
Weight	1 kg (2.20lb)



DIMENSIONS

(Unit - mm)



ACCESSORIES (OPTIONAL)



ACCESSORIES CONFIGURATION TREE

