

DC-E4213WRX 2.8mm | 4.0mm | 6.0mm

- Easy Installation with DirectIP NVR
- Full HD (1080p) Resolution
- Fixed-focal Lens (f = 2.8mm / 4.0 mm / 6.0 mm)
- micro SD / SDHC / SDXC
- Two-way Audio
- Alarm In / Out
- IK10 / IP67 Supports
- PoE (IEEE 802.3af Class 2)
- Day and Night (ICR)
- True Wide Dynamic Range (WDR)
- IR LED (Distance : 30 m / 98.4 ft)
- 3-axis Mechanical Design for Installation
- Supports ONVIF




SPECIFICATIONS


VIDEO	
Image Sensor	1/2.8" CMOS
Max. Resolution	1920 x 1080
Scanning Mode	Progressive Scan
Lens Type	Fixed-focal
Focal Length	f = 2.8mm / 4.0 mm / 6.0 mm
Aperture	F 2.0 (2.8mm) / F2.15 (4.0 mm) / 1.6 (6.0 mm)
Iris Control	Fixed Iris
Angular Field of View	113.74° (H) 61.5°(V) 134.45°(D)) (f = 2.8 mm) 87°(H), 44°(V), 106°(D) (f = 4.0 mm) 53.5° (H) 29.5°(V) 62.16°(D) (f = 6.0 mm)
Min. Illumination	Color : 0.2 Lux @ F2.0 B/W : 0 Lux (IR LED On) (2.8 mm) Color : 0.2 Lux @ F2.15 (4.0 mm) B/W : 0 Lux (IR LED On) (4.0 mm) Color : 0.2 Lux @ F1.6 (6.0 mm) B/W : 0 Lux (IR LED On) (6.0 mm)
Dynamic Range	120dB
Electronic Shutter Speed	Auto / Manual (1/30 ~ 1/10000), Anti-Flicker, Slow Shutter (1~1/5, 1/7.5, 1/15)
Day and Night	IR Cut Filter with Auto Switch
IR Distance (LEDs)	30 m / 98.4 ft (4ea)
Image Setting	Exposure, White Balance, Self-Adjusting Video Mode(Sharpness, Contrast, Colors, Brightness Control)
Backlight Compensation	On / Off
Mirroring / Pivot	Horizontal / Vertical / Pivot
Image Stabilizer	-
De-fog	On / Off
Privacy Masking	8 Zones
Intelligent Video	Video Motion Detection, Active Tampering Alarm, Trip Zone
Video Out	-
NETWORK	
Video Compression	H.265, H.264 (MP) M-JPEG
Intelligent Codec	Supported
Bitrate Control	H.265 - VBR / CBR H.264 - VBR / CBR
Audio Compression	ADPCM 16K, G.726, G.711 u-Law, G.711 a-Law
Two-way Audio	Yes
IP Camera Protocol	DirectIP 2.0, ONVIF
Max. Frame Rate	30ips : 1920 x 1080(WDR)
Supported Resolution	1920x1080, 1280x720, 704x480, 640x360, 352x240
Multi-video Streaming	Quadruple Streaming
Network Protocols	DirectIP 2.0 Protocol, IPv4, IPv6, RTP/RTSP/TCP, RTP/RTSP/HTTP/TCP, RTP/UDP RTSP/TCP, HTTP, HTTPS, FTP, SMTP, FEN, mDNS, Upnp, SNMPv2
Security	SSL Encryption, Multi-user Authority, IEEE 802.1x IP Filtering, HTTPS
Remote Access Client	DirectIP NVR Connection, IDIS Web, IDIS Mobile, IDIS Solution Suite
Ethernet	RJ45 (10/100BASE-T)
Recording Session Buffer(NLTSrec)	Yes (Up to 60MB)
Edge Storage	micro SD / SDHC / SDXC, Smart Failover (Up to 256GB)
ALARM AND EVENT	
Trigger Event	Motion Detection, Alarm in, Audio Detection, Tampering, Trip Zone
Event Notification	Remote S/W, Email (With Image)
Audio In / Out	1 / 1
Alarm In / Out	1 / 1
ENVIRONMENTAL	
Vandal Proof Casing	IK10
Outdoor Ready	IP67
Operating Temperature	-20°C ~ +55°C (-4°F ~ +131°F) *Starting Up at Above 0°C (32°F)
Operating Humidity	0% ~ 90%
ELECTRICAL	
Power Source	PoE (IEEE 802.3af Class 2)
Power Consumption	PoE, IEEE 802.3af(Class 2) , 5.6W
Approvals	FCC, CE, KC
MECHANICAL	
Dimensions	75 mm x 70 mm x 197 mm (2.95" x 2.75" x 7.75")
Weight	0.655 kg (1.44lb)

DIMENSIONS

(Unit - mm)



ACCESSORIES (OPTIONAL)



ACCESSORIES CONFIGURATION TREE

