

5MP IR Fisheye Camera

DC-Y6513RX


- Easy Installation with DirectIP NVR
- 5MP (2560 x 2048) Resolution
- Fixed-focal Lens (f = 1.5 mm)
- micro SD / SDHC / SDXC, Smart Failover (Up to 256GB)
- Two-way Audio
- Alarm In / Out
- PoE (IEEE 802.3af Class 3), 12V DC
- Day and Night (ICR)
- True Wide Dynamic Range (WDR)
- IR LED (Distance : 15 m / 49.2 ft)
- Various viewing composition, 6 dewarping view modes
- Supports ONVIF




SPECIFICATIONS

VIDEO	
Image Sensor	1/1.8" CMOS
Max. Resolution	2560 x 2048
Scanning Mode	Progressive Scan
Lens Type	Fixed-focal
Focal Length	1.5 mm
Aperture	F1.8
Iris Control	Fixed IRIS
Angular Field of View	180°(H), 180°(V), 180°(D)
Pan / Tilt Range	-
Min. Illumination	Color: 0.5 Lux @ F1.8 B/W: 0 Lux (IR LED On)
Dynamic Range	120dB (True WDR)
Electronic Shutter Speed	Auto / Manual (1/30 ~ 1/10000), Anti-Flicker, Slow Shutter (1~1/5, 1/7.5, 1/15)
Day and Night	IR Cut Filter with Auto Switch
IR Distance (LEDs)	15 m / 49.2 ft (6ea)
Image Setting	Exposure, White Balance, Self-Adjusting Video Mode (Sharpness, Contrast, Colors, Brightness Control)
Backlight Compensation	On / Off / HSBLC
Image Stabilizer	-
Privacy Masking	8 Zones
Intelligent Video	Video Motion Detection, Active Tampering Alarm, Trip Zone, Heatmap
Viewing Composition	1O, 1P, 1P2R, 2P, 4R, 1O7R
Video Out	-
NETWORK	
Video Compression	H.265, H.264 (MP), M-JPEG
Intelligent Codec	Supported
Bitrate Control	H.264 - CBR / VBR, H.265 - CBR / VBR
Audio Compression	ADPCM 16K, G.726, G.711 u-Law, G.711 a-Law
Two-way Audio	Yes
IP Camera Protocol	DirectIP 2.0, ONVIF Profile S
Max. Frame Rate	30ips : 2560 x 2048 (WDR)
Supported Resolution	2560x2048, 1920x1536, 2560x1024, 1280x1024, 640x512, 640x256
Multi-video Streaming	Quadruple Streaming
Network Protocols	DirectIP 2.0 Protocol, IPv4, IPv6, RTP/RTSP/TCP, RTP/RTSP/HTTP/TCP, RTP/UDP RTSP/TCP, HTTP, HTTPS, FTP, SNMP, SMTP, FEN, mDNS, uPNP, SNMPv2
Security	SSL Encryption, Multi-user Authority, IEEE 802.1x IP Filtering, HTTPS
Remote Access Client	DirectIP NVR Connection, IDIS Web, IDIS Mobile, IDIS Solution Suite
Ethernet	RJ45 (10/100BASE-T)
Recording Session Buffer (NLSrec)	Yes (Up to 60MB)
Edge Storage	micro SD / SDHC / SDXC, Smart Failover (Up to 256GB)
ALARM AND EVENT	
Trigger Event	Motion Detection, Alarm in, Audio detection, Tampering, Trip Zone
Event Notification	Remote S/W, Email (With Image)
Audio In / Out	1(Built In MIC)+1 / 1
Alarm In / Out	1/1
ENVIRONMENTAL	
Vandal Resistance	-
Outdoor Ready	-
Operating Temperature	-10°C ~ +50°C (+14°F ~ +122°F) *Starting Up at Above 0°C (32°F)
Operating Humidity	0% ~ 90%
ELECTRICAL	
Power Source	12VDC, PoE IEEE 802.3af (Class 3)
Power Consumption	12V=, 0.62A, 7.5W PoE (IEEE 802.3af Class 3), 7.5W
Approvals	FCC, CE, KC
MECHANICAL	
Dimensions	Ø122 x 35.8 mm (Ø4.80" x 1.40")
Weight	0.285 kg (0.63 lb)

DIMENSIONS



ACCESSORIES (OPTIONAL)



ACCESSORIES CONFIGURATION TREE

