

DirectIP 28 Port Gigabit PoE switch

DH-2328PF

- Individual port data transmission to DirectIP NVR
- PoE (IEEE 802.3af, IEEE 802.3at) compliant
- Maximum per-device PoE delivery of 380W available for 1~24 RJ45 ports
- Central power control for greater network utility
- Supports 24 RJ45 ports and 4 SFP slots



SPECIFICATIONS

SYSTEM	
CPU	1Ghz single core
System Memory	512MB SDRAM, 256MB Flash
Switching Capacity	56Gbps
CONNECTIVITY	
Copper Service Port	24 RJ45 Connectors (10/100/1000BASE-T)
Copper Uplink Port	-
Optical Uplink Port	4 SFP Slot (1000BASE-X)
PoE POWER	
Supported Standards	IEEE 802.3af-2003 / IEEE 802.3at-2009
PD Connection	Up to 24 IEEE 802.3af PDs or Up to 12 IEEE 802.3at PDs
PSE Power	54.5VDC, 600mA, PoE 24 ports, max. 380W
GENERAL	
Dimensions (W x H x D)	440mm x 44mm x 260mm (17.3" x 1.7" x 10.2")
Weight	4.28kg (9.42lb)
Operation Temperature	0°C to +50°C (-32°F- 122°F)
Power Input	AC100-240V, 50-60Hz, 5.5A-2.5A
Power Consumption	max 460W
Approvals	FCC, CE, KC

DIMENSIONS

(Unit - mm)

