

Premium wide LCD Monitor (10 inch)

- BNC, RTSP, VGA, Audio
- 3D comb filter, noise reduction
- Auto power recovery, multi-language support, trigger sensor
- 75x75mm VESA mount support
- 30,000 hours lifetime
- RJ-45 (2CH input)
- NDAA Compliance



SPECIFICATIONS

VIDEO	
Screen Size	10.1 Inch
Max. Resolution	1280 x 800 @ 60Hz
Pixel Pitch	0.1695 x 0.1695mm
Brightness	350cd / m2
Contrast Ratio	800 : 1
Aspect Ratio	16 : 10
Viewing Angle (H/V)	170° / 170°
Display Color	8bits / 16.7 Million
Response Time	< 15ms (Gray to Gray)
Video System	NTSC / PAL
LifeTime(Typ.)	30,000Hrs
Interface (Cable type)	
Video In	1 In
RTSP (LAN)	RJ-45 (2CH input)
VGA In (15Pin D-Sub)	-
Audio In (RCA Type)	-
PC Stereo In	-
Transmitter	
Remote Control	Yes
Audio	
Built-in Speakers	-
Features	
Filter Type	3D Comb Filter
Deinterlacing	Yes
Advanced Auto Power Recovery	Yes
Noise Reduction Control (NR)	Yes
LCD Protection Glass	N/A
Auto Pixel Shift	Yes
Auto Source Sequencing	Yes
Trigger Sensor	2 In
Multi Language	English, Spanish, French, German, Italian
General	
Outline Dimension (w / stand)	260.6mm x 177mm x 70mm (10.2" x 6.9" x 2.75")
Net Weight	Appx. 4 Kg
Material / Color	Electronic galvanized iron / Black
Desk Top Stand	-
Consumption: < On	DC 9~36V / < 11W
Operating Temperature	0°C ~ 40°C / 32° ~ 104°F
Storage Temperature	-20°C ~ 60°C / -4° ~ 140°F
Mounts	
VESA Mount Size	75 x 75mm (2.9" x 2.9")

ADVANTAGES



Before 3D Comb Filter



After 3D Comb Filter

In signal processing, a comb filter adds a delayed version of a signal to itself, causing constructive and destructive interference. The frequency response of a comb filter consists of a series of regularly-spaced spikes, giving the appearance of a comb

DIMENSIONS

Unit - mm (inch)

