

# Premium wide LCD Monitor (19 inch)

- BNC, HDMI, VGA, Audio
- 3D comb filter, noise reduction
- Auto power recovery, multi-language support, optional trigger sensor
- 100x100mm VESA mount support
- 40,000 hours lifetime
- Response Time (Less than 14ms)
- NDAA Compliance



## SPECIFICATIONS

VIDEO	
Screen Size	19 Inch
Max. Resolution	1280 x 1024 @ 75Hz
Pixel Pitch	0.294 x 0.294mm
Brightness	250cd / m2
Contrast Ratio	1000 : 1
Aspect Ratio	5 : 4
Viewing Angle (H/V)	178° / 178°
Display Color	8bits / 16.7 Million
Response Time	< 14ms (Gray to Gray)
Video System	NTSC / PAL
LifeTime(Typ.)	40,000Hrs
Interface (Cable type)	
Video In	1 In
RTSP (LAN)	1 In
VGA In (15Pin D-Sub)	-
Audio In (RCA Type)	-
PC Stereo In	-
Transmitter	
Remote Control	Yes
Audio	
Built-in Speakers	-
Features	
Filter Type	3D Comb Filter
Deinterlacing	Yes
Advanced Auto Power Recovery	Yes
Noise Reduction Control (NR)	Yes
LCD Protection Glass	Option
Auto Source Sequencing	Yes
Trigger Sensor	-
Multi Language	English, Spanish, French, German, Italian
General	
Outline Dimension (w / stand)	412.2mm x 340.78mm x 45mm (16.2" x 13.3" x 1.73")
Net Weight	6.25 Kg (13.78 lbs)
Material / Color	Metal / Black
Desk Top Stand	-
Consumption: < On	DC 9V~36V
Operating Temperature	0°C ~ 40°C / 32° ~ 104°F
Storage Temperature	-20°C ~ 60°C / -4° ~ 140°F
Mounts	
VESA Mount Size	100 x 100mm (3.9" x 3.9")

## ADVANTAGES



Before 3D Comb Filter



After 3D Comb Filter

In signal processing, a comb filter adds a delayed version of a signal to itself, causing constructive and destructive interference. The frequency response of a comb filter consists of a series of regularly-spaced spikes, giving the appearance of a comb

## DIMENSIONS

Unit - mm (inch)

