

TC-D4211RX 2.8mm

- Full HD (1080p) Resolution
- Fixed-focal Lens (f=2.8mm)
- Day and Night (ICR)
- True wide Dynamic Range (WDR)
- Motion Detection
- De-fog
- HLC
- Coaxial OSD Control



SPECIFICATIONS

VIDEO	
Image Sensor	1/2.8" CMOS Sensor
Effective Pixels	1945(H) x 1097(V), 2.13M Pixels
Total Pixels	1945(H) x 1109(V), 2.16M Pixels
Max. Resolution	1920 x 1080
Scanning Mode	Progressive Scan
Lens Type	Fixed-focal
Focal Length	f = 2.8mm
Aperture	F = 1.6
Iris Control	Fixed Iris
Angular Field of View	106.5°(H), 57.5°(V), 122.7°(D)
Pan / Tilt Range	Pan : 0° ~ 360° Tilt : -5° ~ 60° Rotate: 0° ~ 360°
Min. Illumination	Color : 0.1 Lux @ F 1.6 B/W : 0 Lux (IR LED On)
S/N Ratio	More than 50dB
Dynamic Range	120dB (True WDR)
Electronic Shutter Speed	Auto / Manual (1/30, 1/25Sec ~ 1/30000Sec) / FLICKER
Day and Night	Yes (ICR)
IR Distance (LEDs)	15m / 49.2ft (24ea)
Video Out	1 HD BNC
FUNCTION	
AGC	0 ~ 10 Level Adjustable
Brightness	0 ~ 20 Level Adjustable
Sens-up	Off / x2 ~ x32
Wide Dynamic Range (WDR)	Off / On (Low, Middle, High)
Backlight Compensation (BLC)	Off / On
HLC	1 ~ 20 Level Adjustable (All day / Night only)
ACE(D-WDR/ATR-EX)	-
Motion Detection	Off / On (4 Zone)
Privacy Masking	Off / On (16 Zone)
Day and Night	Auto(AGC) / Color / B&W / Extern
Smart IR (IR Optimizer)	0~20 Level Adjustable
White Balance	Auto / Autoext / Preset / Manual (3000, 5000, 8000)
Digital Noise Reduction	Off / Low / Middle / High
Mirror	Mirror, Flip
D-ZOOM (EZOOM)	-
Sharpness	0~10 Level Adjustable
De-fog	Off / On
GAMMA Correction	r = 0.45 ~ 0.75
Lens Shading (LSC)	-
Language	ENG / CHN / CHN(S) / JPN / KOR
ENVIRONMENTAL	
Outdoor Ready	-
Storage Temperature	-20°C ~ +60°C (-4°F ~ +140°F) (Humidity : 0% ~ 95%)
Operating Temperature	-10°C ~ +50°C (14°F ~ +122°F) (Humidity : 0% ~ 90%)
ELECTRICAL	
Power Source	DC 12V
Power Consumption	5W
MECHANICAL	
Dimensions (W x H x D)	Ø112.1mm x 88.3mm (Ø4.41" x 3.48")

DIMENSIONS



ACCESSORIES (OPTIONAL)



ACCESSORIES CONFIGURATION TREE

