

TR-4308

- Supports Multi Standard Analog Camera
- Up to 240ips Full HD recording
- Up to 5MP resolution support
- UHD Display with HDMI output
- Full HD Display with HDMI and VGA output
- Supports CVBS Spot Monitor
- Long transmission distance over coax cable
- Supports HD-TVI camera OSD control over coax
- Expandable up to 48TB using 4 SATA interfaces and 1 eSATA storage interface
- Supports one click network configuration through FEN service





SPECIFICATIONS

VIDEO	
Video Inputs	8 BNC (Multistandard Analog)
Supported Camera Types	5MP, 4MP, 3MP, 1080P30, 1080P25, 720P30, 720P25, CVBS (NTSC / PAL)
Video Outputs	1 HDMI, 1 VGA, 1 BNC (Spot)
Display Resolution	HDMI : 3840 x 2160, 1920 x 1080, 1440 x 900, 1280 x 1024 VGA : 1920 x 1080, 1440 x 900, 1280 x 1024 Composite : 720 x 480 (NTSC) , 720 x 576 (PAL)
Display Speed	Up to 240ips
Digital Zoom	x2 ~ x12
RECORDING	
Recording Resolution	5MP, 4MP, 3MP, 1920 x 1080, 1280 x 720, 960 x 480, 720 x 480, 960 x 240, 720 x 240, 480 x 240, 360 x 240
Frame Rate	240ips @ 1080p
Compression	H.264
Recording Mode	Time-lapse, Event, Pre-event, Panic
Trigger Events	Alarm In, Motion Detection, Video Loss, Text-in
PLAYBACK	
Performance	4ch 1080p Synchronous Playback
Search Mode	Time-lapse, Event Log, Motion, Text-in
Digital Zoom	x2 ~ x12
STORAGE	
HDD	SATA x 4, eSATA x1 (Up to 6TB Capacity for Each Disk)
Total Capacity	48TB = 6TB x (4 + (1 x 4))
Data Export Device	USB HDD, USB Stick
NETWORK	
Client Connection	Gigabit Ethernet x 1
Transmission Speed	120ips @ Full HD
Remote Data Export	IDIS Player, AVI, JPG
Event Notification	Email (Attach Clip (.cbf)), Callback to Remote S/W, Push Notification (IDIS Mobile), SNS (Twitter), NetFS (FTP)
Two-way Audio	Yes
Client Viewer	IDIS Center, IDIS Mobile, IDIS Web
INTERFACE	
Audio In / Out	4 RCA / 1 RCA + 1 HDMI
Alarm In / Out	8 In / 4 Relay Out
Alarm Reset In	1
Serial Interface	RS232, RS485 (Terminal Block), USB 2.0, USB 3.0
User Interface	Mouse, IR Remote Control, Front Button, Network Remote Keyboard
GENERAL	
Operating System	Embedded Linux
Unit Dimensions (W x H x D)	430mm x 88mm x 413mm (16.9" x 3.5" x 16.3")
Unit Weight	6.0kg (13.2lb) (With 1 HDD)
Operating Temperature	0°C ~ 40°C (32°F ~ 104°F)
Operating Humidity	0% ~ 90%
Power Input	AC 100-240 V, 50/60Hz, 1.2 - 0.6A
Power Consumption	76W
Approvals	FCC, CE, KC, CB, UL, PSE

DIMENSIONS

(Unit - mm)



- 1 Video Input
- 2 Alarm Connection Ports
- 3 RS-485 Port
- 4 RS-232 Port
- 5 eSATA Port
- 6 Factory Reset Button
- 7 SPOT / HDMI / VGA Out Port
- 8 Network Port
- 9 Audio In / Out
- 10 Power In Port