


DV-1304-A





# Featured benefits of IDIS AI Box

Introducing industry's only IDIS AI Box in various benefits





# In-house develop AI engine (IDIS Deep Learning Engine)

Developed by our own R&D team, the IDIS AI engine is designed to specifically tackle the challenges of security and surveillance operations.

By training the IDIS Deep Learning Engine on vast data sets, the AI Box delivers up to 98% accurate alerts and notifications compared to conventional video analytics.

This means that users have the flexibility to configure Al around their own specific security, safety, and other operational needs.



# **Low Total Cost of Ownership**

# No upfront or recurring licenses

Users can take advantage of industry-leading accurate video analytics without any license fees or devices connection costs.

# **Empower your existing cameras**

There's no need to buy new AI edge cameras, expensive AI NVRs, or hardware. Reap all the benefits of industry-leading AI functionality, by simply adding the AI Box to your existing IDIS system.

# **Proactive monitoring and less human error**

Al-powered analytics reduce false alarms and eliminate the need to continually monitor multiple video streams that lead to operator fatigue, and events being missed.



# Free yet feature-rich video management

Users can benefit from the industry's only full-featured, free VMS, IDIS Center, that gives users live monitoring, playback, and highly efficient forensic search to speed up investigations.



# **NDAA Compliant**

The IDIS DV-1304-A is part of the IDIS suite of NDAA-compliant products, which are trusted for use in US federal agency or funded projects, Department of Defense (DoD) applications, and for the sale and implementation by associated contractors.



# A Simple Add-On Al Box Using **DirectlP**®


# Leverage existing legacy systems of any size

The IDIS all-in-one AI Box, DV-1304-A is license free and comes pre-installed with the IDIS Deep Learning Engine that delivers up to 98% accuracy. It packs a punch with all the Al-powered functionality that users need to reduce false alarms and take a proactive approach to strengthening security and safety.

It comes as a simple add-on appliance compatible with existing IDIS network cameras and recorders, eliminating the need to implement complex analytics software or upgrade to edge cameras. Users can leverage their investments in various IDIS camera models by simply connecting the DV-1304-A to existing NVRs or adopt it as part of a next-gen IDIS end-to-end surveillance solution.


Customers benefit from intuitive management via the costfree IDIS Center VMS with the scalability to analyze multiple channels simultaneously by connecting additional boxes to their choice of IDIS NVRs. The DV-1304-A is optimized to minimize storage and bandwidth requirements, while enabling highly efficient event search.







# Affordable Al Box Designed to Meet The Demands of Small to Large Applications






- The DV-1304-A is easily scalable to meet the needs of larger customers by simply adding additional appliances to existing systems.
- Users can analyze as many channels as they need by connecting more boxes to their choice of IDIS NVRs, using the simplicity of DirectIP plug-and-play protocols and configuration settings.
- Fully integrated into a single IDIS system the AI Box is easily configured and maintained with firmware updates via NVRs.



# **Video Surveillance**

# Essential Al-powered functionality that delivers real-time accurate alerts












# **SPECIFICATIONS**

DV-1304-A	
Video	
Video Inputs	4 IP Channels
Supported Device	DirectIP NVR
VA Support	Object Detection, Intrusion, Loitering, Line Crossing, Face Detection
Networkw	
Video Compression	H.265, H.264
Network Connection	100 M Ethernet x 1 (100Base-TX) with PD 100 M Ethernet x 1 (100Base-TX) with PSE (PSE need Adaptor)
Environmental	
Operating Temperature	0°C to 40°C (32°F to 104°F)
Operating Humidity	0% ~ 90%
Electrical	
Power Input	48 V=, PoE
Power Consumption	48 V=, 0.8 A, 38.4 W PoE, IEEE 802.3 at(Class 4), 25 W DC OUTPUT : 48 V=, 0.35 A MAX
Approval	FCC, CE, KC
Mechanical	
Unit Dimensions (W x H x D)	200 mm x 44 mm x 157.6 mm (7.9" x 1.7" x 6.2")
Unit Weight	0.88 kg (1.94 lb)



# Add-On 4-Channel Surveillance Al Box

Packed with highly accurate, in-house developed Al-powered analytics





One Solution. One Company.

### **IDIS HQ**

IDIS Tower, 344 Pangyo-ro Bundang-gu, Seongnam-si Gyeonggi-do, 13493 Republic of Korea

- +82 (0)31 723 5400
- F +82 (0)31 723 5100
- sales@idisglobal.com

## **IDIS** America

801 Hammond Street Suite 200 Coppell, TX 75019

- 1 469 444 6538
- +1 469 464 4449
- sales\_americas@idisglobal.com

## IDIS Europe

1000 Great West Road Brentford, Middlesex TW8 9HH United Kingdom

- 1 +44 (0)203 657 5678
- +44 (0)203 697 9360
- uksales@idisglobal.com

IDIS and identifying product names and numbers herein are registered trademarks of IDIS Co., Ltd. All non-IDIS brands and product names are trademarks or registered trademarks of their

# **IDIS Middle East**

P.O. Box 341037 D-308, DSO HQ Bldg Dubai Silicon Oasis Dubai, U.A.E.

- 1 +971 4 501 5434
- F +971 4 501 5436
- sales\_mena@idisglobal.com

### Turkish Liaison Office

- +90 533 696 7780
- 📵 sales\_mena@idisglobal.com

### **IDIS Netherlands**

De Slof 9 5107 RH Dongen The Netherlands

EU Distribution Center ID

- 1 +31 (0)162 387 217

### IDIS Benelux

- +31 (0)162 387 247
- sales@bnl.idisglobal.com

respective companies. Product appearance, build status, and/or specifications are subject to change without notice. Copyright © IDIS Co., Ltd. All rights reserved.

\* Product specifications in this brochure can change. Please confirm details on our website.



